



WWW.KINSPIRE-ENERGY.COM




36 Cells
Mono-crystalline

150-170W
Power output

17.2%
The Highest Efficiency

0~+5W
Tolerance

0.5% Annual Degradation over 30 years



RS6E-M

RS6E-M is a robust solar module with 36 solar cells. These modules can be used for on-grid solar applications. Our meticulous design and production techniques ensure a high-yield, long-term performance for every module produced. Our rigorous quality control and in-house testing facilities guarantee Resun Solar's modules meet the highest quality standards possible



High module conversion efficiency (up to 17.2%), through superior manufacturing technology



Guaranteed 0~+5W positive power output tolerance ensures high reliability



Anti-reflective, hydrophobic coating improves light absorption and reduces surface dust



Excellent performance under low light environments (mornings, evenings and cloudy days)



Suitable for harsh environments, such as coasts, deserts and lakes. Withstand high level of wind loads (2400pa) and snow loads (5400pa)


Full range of products and certification systems

ISO 9001 TUV PID-FREE CE IEC61215/61730/61701/62716



LINEAR PERFORMANCE WARRANTY
12 year Product Warranty / 30 year Linear Power Warranty

Dimension of PV Modules Unit: mm



ELECTRICAL DATA(STC)

Rated Power in Watts-Pmax(Wp)	150W	160W	170W
Open Circuit Voltage-Voc(V)	22.7V	23.7V	24.5V
Short Circuit Current-Isc(A)	8.58A	9.08A	9.58A
Maximum Power Voltage-Vmp(V)	18.4V	18.74V	18.88V
Maximum Power Current-Imp(A)	8.16A	8.60A	9.26A
Module Efficiency (%)	15.16%	16.20%	17.20%

STC: Irradiance 1000 W/m², Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.

ELECTRICAL DATA(NOCT)

Maximum Power-Pmax (Wp)	112W	120W	128W
Open Circuit Voltage-Voc (V)	20.62V	20.90V	21.1V
Short Circuit Current-Isc (A)	7.12A	7.23A	7.34A
Maximum Power Voltage-Vmp(V)	17.14V	17.25V	17.36V
Maximum Power Current-Imp(A)	6.55A	6.66A	6.78A

NOCT: Irradiance at 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s.

MECHANICAL DATA

Solar cells	Mono-crystalline 156.75x156.75mm, 5 Bus bars
Cell configuration	36 cells(4x9)
Module dimensions	1487x666x35mm
Weight	11.5KGS
Front Cover	3.2mm Tempered Glass
Frame Material	Anodized Aluminum Alloy
J-BOX	IP65 or IP67, 2 or 3 Diodes
Cable	4mm ² (IEC)/12AWG(UL),900mm
Connectors	MC4 or MC4 Comparable
Standard Packaging	2pcs/carton


TEMPERATURE & MAXIMUM RATINGS

Nominal Operating Cell Temperature (NOCT)	45°C±2°C
Temperature Coefficient of Voc	-0.32%/°C
Temperature Coefficient of Isc	0.05%/°C
Temperature Coefficient of Pmax	-0.39%/°C
Operational Temperature	-40~+85°C
Maximum System Voltage	1000V(IEC)/600V(UL)
Max Series Fuse Rating	15A
Limiting Reverse Current	15A

PACKAGING CONFIGURATION

	40HQ	20GP
Modules per container	1680pcs	660pcs
Package	2pcs/carton	2pcs/carton
Package Number	840carton	330carton

I-V characteristics at different irradiancies



I-V characteristics at different temperature

